

## Farmax Spaders

[www.spaders.com.au](http://www.spaders.com.au)

Operational working suggestions  
for the **best** outcome

- Know your soil profile
- Pre ripping improves the mixing
- Level the big furrows after delving  
and before spading
- Spade at 20 – 50 degree angle across  
the ripping / delving
- Deeper spading needs slower speed



## Grocock Soil Improvement

**PO Box 484  
Bordertown SA 5268**

**Phone: 08 8754 6025  
Mobile: 0427 546 025  
Email: [grooks@internode.on.net](mailto:grooks@internode.on.net)  
Website: [www.spaders.com.au](http://www.spaders.com.au)**

## Farmax Spaders 4.5m trailing machine

**Grocock Soil Improvement Pty Ltd**




The Farmax spader is a digging machine which mixes soil thoroughly to a depth of 200 – 400mm incorporating clay, lime, stubble, green manure, fertilizer and / or trace elements.

[www.spaders.com.au](http://www.spaders.com.au)



With the introduction of the Farmax 4.5m machine a new generation of digging machines is created.



Bolt on spades allow easier replacement and the bolts give some shearpin protection.

Standard with PTO slip clutch. PTO drive line allows sharp turns while rotor is operating clear of the ground.

Press wheels carry back of machine giving some compaction with defined ridges which help to resist wind erosion.

## Technical data

## 4.5m machine

Working width	4.5m
Number spades	36
Weight	6800kg
PTO Power	200 - 300 Hp 149—224 kw
Gearbox / Differential rated	300 Hp
Capacity	Up to 3.4 ha/h Up to 7.5 km/h
Working depth	200 - 400 + mm
PTO rpm	1000 rpm
Press wheels	8.3 x 24" tractor tread tyres 2 gangs of 8 wheels each



Seeding and spading in one pass



Defined ridges behind 4.5m Farmax Spader

Grocock Soil Improvement Pty Ltd

PO Box 484  
Bordertown SA 5268

Phone: 08 8754 6025  
Mobile: 0427 546 025

Email: [grooms@internode.on.net](mailto:grooms@internode.on.net)  
Website: [www.spaders.com.au](http://www.spaders.com.au)